

PRODUCT SPECIFICATIONS		LUXURY COLLECTION
Waterproof	100%	
Total thickness	6.5mm	
Thickness per layer	0.7mm wearlayer + 5 mm SPC core + 1.5mm pad	
Locking System	Uniclick	
Color Variation	V3 High Level	
Installation	Click	
Bottom and core material	SPC	
Radiant Heat System	Limited	
Moisture Content	<=10%	
High-Low Temperature Cycle	(ASTM D1211) : 10-50°C	
Hardness of Coating	(ASTM D3363-05) : 2H	
Abrasion Resistance	(AST 4060 S33) : 100 cycles	
Scratch Resistance	(EN 438-2): 3N	
Coating Adhesion	(ASTM D3359-2009) : 5B	
Deviation of length/Width/Thickness	length: ±1mm; width: ±0.1mm; thickness: ±0.2mm	
Bow (Convex and Concave)	1% of the length	
Cup (Convex and Concave)	0.5% of the length	
Average Length Per Box	1254mm	
Longest length quantity per box	10 Pieces	
How many length in one box	60°	
Certification	Floor Score (copy on request)	
Warranty	Lifetime structural and 25 years finish	
Slip resistance impact insulation	R10	
Sound insulation	IIC 73	
Waterproof	STC 72	