

| PRODUCT SPECIFICATIONS              | RENAISSANCE COLLECTION                         |
|-------------------------------------|--|
| Waterproof                          | 100%   |
| Total thickness                     | 5.5mm  |
| Thickness per layer                 | 0.3mm wearlayer + 3.7mm SPC core + 1.5mm pad   |
| Locking System                      | Uniclick                                       |
| Color Variation                     | V3 High Level                                  |
| Installation                        | Click  |
| Bottom and core material            | SPC  |
| Radiant Heat System                 | Limited  |
| Moisture Content                    | <=10%  |
| High-Low Temperature Cycle          | (ASTM D1211 ): 10-50°C (AST D3363-05: 2H       |
| Hardness of Coating                 | (ASTM 4060 S33 ) : 100 cycles                  |
| Abrasion Resistance                 | (EN 438-2): 3N                                 |
| Scratch Resistance                  | (AST D3359-2009 ) : 5B                         |
| Coating Adhesion                    | length: ±1mm; width: ±0.1mm; thickness: ±0.2mm |
| Deviation of length/Width/Thickness | 1% of the length                               |
| Bow ( Convex and Concave )          | 0.5% of the length                             |
| Cup ( Convex and Concave )          | 1525mm   |
| Average Length Per Box              | 8 Pieces                                       |
| Longest length quantity per box     | 60°  |
| How many length in one box          | Floor Score ( copy on request)                 |
| Certification                       | Lifetime structural and 25 years finish        |
| Warranty                            | RIO  |
| Slip resistance impact insulation   | [IC 73   |
| Sound insulation                    | STC 72   |
| Waterproof                          | 100%   |